



Arranging Shoes

Adnan owns the biggest shoe store in Baku. A box containing n pairs of shoes has just arrived at the store. Each pair consists of two shoes of the same size: a left and a right one. Adnan has put all of the $2n$ shoes in a row consisting of $2n$ **positions** numbered 0 through $2n - 1$ from left to right

Adnan wants to rearrange the shoes into a **valid arrangement**. An arrangement is valid if and only if for every i ($0 \leq i \leq n - 1$), the following conditions hold

- The shoes at positions $2i$ and $2i + 1$ are of the same size
- The shoe at position $2i$ is a left shoe
- The shoe at position $2i + 1$ is a right shoe

For this purpose, Adnan can make a series of swaps. In each swap, he selects two shoes that are **adjacent** at that moment and exchanges them (i.e., picks them up and puts each one on the former position of the other shoe). Two shoes are adjacent if their positions differ by one

Determine the minimum number of swaps that Adnan needs to perform in order to obtain a valid arrangement of the shoes

Implementation details

You should implement the following procedure

```
int64 count_swaps(int[] S)
```

an array of $2n$ integers. For each i ($0 \leq i \leq 2n - 1$), $|S[i]|$ is a non-zero value equal to the size of the shoe initially placed at position i . Here, $|x|$ denotes the absolute value of x , which equals x if $x > 0$ and equals $-x$ if $x < 0$. If $S[i] < 0$, the shoe at position i is a left shoe; otherwise, it is a right shoe

This procedure should return the minimum number of swaps (of adjacent shoes) that need to be performed in order to obtain a valid arrangement

Examples


Example 1

:Consider the following call

```
count_swaps([2, 1, -1, -2])
```

.Adnan can obtain a valid arrangement in 4 swaps

For instance, he can first swap shoes 1 and -1 , then 1 and -2 , then -1 and -2 , and finally 2 and -2 . He would then obtain the following valid arrangement: $[-2, 2, -1, 1]$. It is not possible to obtain any valid arrangement with less than 4 swaps. Therefore, the procedure `count_swaps` should return



Example 2

:In the following example, all the shoes have the same size

```
count_swaps([-2, 2, 2, -2, -2, 2])
```

Adnan can swap the shoes at positions 2 and 3 to obtain the valid arrangement

.1 $[-2, 2, -2, 2, -2, 2]$, so the procedure should return

Constraints

- $1 \leq n \leq 100\,000$
- For each i ($0 \leq i \leq 2n - 1$), $1 \leq |S[i]| \leq n$
- A valid arrangement of the shoes can be obtained by performing some sequence of swaps

Subtasks

- .1 $n = 1$ (points 10)
- .2 $n \leq 8$ (points 20)
- .3 (points) All the shoes are of the same size 20
- .4 (points) All shoes at positions $0, \dots, n - 1$ are left shoes, and all shoes at positions $n, \dots, 2n - 1$ are right shoes. Also, for each i ($0 \leq i \leq n - 1$), the shoes at positions i and $i + n$ are of the same size 15
- .5 $n \leq 1000$ (points 20)
- .6 (points) No additional constraints 15

Sample grader

:The sample grader reads the input in the following format

- n :1 line
- $S[0] S[1] S[2] \dots S[2n - 1]$:2 line

.The sample grader outputs a single line containing the return value of `count_swaps`